

5-5/8" Diameter Totally Enclosed Outdoor Sleeve Bearing Fan Motors



Condensers - Heat Pump - Refrigeration



Features:

- All Angle Mount
- Ext. Thru Bolts – Both Ends
- Sleeve Bearing
- 26" Leads
- Auto Protector
- 1/2" Dia. Shaft – Dbl. Flat
- 48 Frame (5-5/8" Dia.)
- Class "B" Insulation
- Permanent Split Capacitor
- 60° C Ambient
- Energy Efficient
- 4, 6 & 8-Pole
- 60 HZ
- Reversing Plug

"Turn-A-Bout" 1 and 2-Speed

Mfg Part No	HP	RPM	Speeds	Volts	Amps		Capacitor (V)
					Rated	Max	
FSE1016SV1	1/6	1075	1	208-230	0.9	1.3	5-370
FSE1026SV1	1/4	1075	1	208-230	1.3	1.8	5-370
FSE1036SV1	1/3	1075	1	208-230	1.8	2.8	7.5/370
FSE1056SV1	1/2	1075	1	208-230	2.8	4.0	10/370
FSE1076SV1	3/4	1075	1	208-230	4.2	5.2	15/370

825 RPM - Single Speed

Mfg Part No	HP	RPM	Speeds	Volts	Amps		Capacitor (V)
					Rated	Max	
FSE1018S	1/6	825	1	208-230	1.1	1.6	5/370
FSE1028S	1/4	825	1	208-230	1.5	1.9	5/370
FSE1038S	1/3	825	1	208-230	1.8	2.4	7.5/370
FSE1058S	1/2	825	1	208-230	2.7	3.7	10/370

5-5/8" Diameter Outdoor Sleeve Bearing Fan Motors



Condensers - Heat Pump - Refrigeration

Conservationist (Capacitor Not Included)



Features:

- Auto Protector
- Class "B" Insulation
- Closed Except Lead End
- Energy Efficient
- Ex. Thru Bolt, Sh. End
- Reversing Plug
- Shaft Slinger
- Sleeve Bearing
- PSC
- Vert. Shaft Up or Horiz. Mount
- 1/2" Dia. Shaft – Dbl. Flat
- 6 & 8 Pole
- 26" Leads
- 48 Frame (-5/8" Dia.)
- 60 Degree C Max. Ambient
- 60 Hz

Mfg Part No	HP	RPM	Speeds	Volts	Amps		Capacitor (V)
					Rated	Max	
FS1026S	1/4	1075	1	208-230	1.5	1.9	5/370
FS1037S	1/3	1075	1	208-230	1.9	2.6	5/370
FS1056S	1/2	1075	1	208-230	3.6	4.4	5/370
FS1076S	3/4	1075	1	208-230	4.0	5.0	10/370

A.O. SMITH



A.O. SMITH

5-5/8" Diameter Standard Efficiency Indoor Blower Motors



Furnaces - Air Handlers - Blowers

Standard Efficiency, Replaces GE 3583, 84, 85, 86, 87, 88, 89, 90 (Capacitor Not Included)



Features:

- Auto Protector
- Class "B" Insulation
- Continuous Air Over
- Lead Reversible
- Open Construction
- PSC
- Ring Adapters
- Sleeve Bearing
- Standard Efficiency
- 2-1/4" Rings with 2-1/2" Adapters Included
- 26" Leads
- 48 Frame (5-5/8" Dia.)
- 60 Hz Only
- 40 Degree C Ambient

Mfg Part No	HP	RPM	Speeds	Volts	Amps		Capacitor (V)
					Rated	Max	
DL1026	1/4	1075	3	115	3.5	4.6	5/370
DL1036	1/3	1075	3	115	4.9	6.4	7.5/370
DL1056	1/2	1075	3	115	6.5	9.0	10/370
DL1076	3/4	1075	3	115	8.9	10.3	15/370
D1026	1/4	1075	3	208-230	1.8	2.2	5/370
D1036	1/4	1075	3	208-230	2.6	3.1	5/370
D1056	1/4	1075	3	208-230	3.2	4.3	7.5/370
D1076	1/4	1075	3	208-230	4.0	5.0	10/370

5-5/8" Diameter High Efficiency Indoor Blower Motors



Furnaces - Air Handlers - Evaporators

Conservationist (Capacitor Not Included)



Features:

- Auto Protector
- Continuous Air Over
- High Efficiency
- Multiple Mount
- Open Construction
- PSC
- Reversing Plug
- Sleeve Bearing
- 1/2" Dia. - Flatted Shaft
- 2-1/4" to 2-1/2" Resilient Rings
- 26" Leads (Minimum)
- 40 Degree C Ambient
- 48 Frame (5-5/8" Dia.)
- 60 Hz

Mfg Part No	HP	RPM	Speeds	Volts	Amps		Capacitor (V)
					Rated	Max	
BDL1106	1	1075	3	115	12.3	14.0	20/370
BD1106	1	1075	3	208-230	5.1	6.5	20/370

Split Phase Resilient Base Motors



Belt Drive and Blower Applications

Split Phase - NEMA and Unity Service Factor



Features:

- Class "B" Ins.
- Continuous Duty
- Energy Efficient
- Open and TEAO
- Reversible
- Sleeve & Ball Bearing
- 60 Hz

Mfg Part No	HP	RPM	Volts	Amps		Frame	Bearings	Protector
				F.L.	S.F.			
GF2024	1/4	1725	115	4.6	1.35	48/56	Sleeve	Auto
GF2034	1/3	1725	115	5.9	1.35	48/56	Sleeve	Auto

Albany, NY	518-489-0010	Rochester, NY	585-482-3876	Allentown, PA	610-437-9818	Scranton, PA	570-346-1565
Binghamton, NY	607-724-2451	Syracuse, NY	315-475-3131	Altoona, PA	814-941-7617	Stroudsburg, PA	570-424-5724
Buffalo, NY	716-853-1291	Utica, NY	315-732-4077	Erie, PA	814-459-4559	Wilkes-Barre, PA	570-824-8779
Middletown, NY	845-733-5666			Harrisburg, PA	717-558-0828	Williamsport, PA	570-323-4606

Oil Burner Motors



Split Phase, 60 Hz, Enclosed, Manual Protector, Factory Connected for CW Rotation




Applications:

Domestic high and low pressure oil burners and other applications where 48M and 48N flange mounting is required. This line of motors includes open (enclosed except for shaft end bracket) and totally enclosed designs to meet all requirements. All mounting dimensions such as location of ears, diameter of rabbit fit and shaft size are in accordance with NEMA standards. Most of the normally stocked replacement ratings feature the external reversing switch for ease of use in those tight, dark and dirty locations. All ratings include sleeve bearings for quiet operation and manual reset thermal overload protectors for safe, dependable use.

Mfg Part No	HP	RPM	Volts	F.L. (Amps)	Frame	Bearings	Rotation
EL2005	1/8	1725	115	2.5	48N	Sleeve	CWLE
EL2002	1/7	3450	115	2.5	48M	Sleeve	CWLE
EL2002V1	1/7	3450	115	2.5	48M	Sleeve	CWLE
EL2014	1/6	1725	115	3.2	48N	Sleeve	REV
EL202	1/4	3450	115	3.4	48N	Sleeve	REV

Switchless - OEM Replacement for Beckett



The new switchless design eliminates the use of an internal starting switch and governor for greater dependability. Use of a PSC design allows for higher efficiencies with 40% lower amp draw. Cooler operation results in fewer failures and reduced service calls. Ball bearings provide smooth, quiet operation and extended motor life. 5-year warranty!

Replaces:

- Beckett 21805U
- Carlin 98022S
- Marathon 0701
- Emerson 3248
- AFI/AFG Burners
- B2001, B2002, B2003, B2004 Chassis

Mfg Part No	HP	RPM	Volts	F.L. (Amps)	Frame	Bearings	Rotation
OBK6002	1/7	3450	115	1.7	48M Flange	Ball	CCWLE

A.O. SMITH

We've got the information you're looking for!

Visit our web site at www.MeierSupply.com

At www.MeierSupply.com, we have a wealth of data available 24 hours a day!

- **Business & technical articles**
- **The Meier Minute newsletter**
- **Contact information for our branches**
- **Technical tips**
- **Product updates and branch training**
- **Links to vendors**
- **Employment opportunities**
- **Box load calculation**

