

# FURNAS CONTACTORS

## Definite Purpose Contactors



### Class 42: 2, 3 and 4 Pole 25-60 Amp Contactors




FEATURES

- Compact size
- Interchangeable mounting
- Straight thru wiring
- Sems screws available on 25A, 30A, and 40A
- Binding Head Screws option on 40A
- Class H Coil Insulation on 25-60 amp
- Meets ARI-780, UL and CSA Standards

Order No	FLA	240V LRA	480V LRA	600V LRA	Poles
42AF35A*	25	150	125	100	3
42BF15A*	30	180	150	120	2
42BF35A*	30	180	150	120	3
42CF35A*	40	240	200	160	3
42CF25A*	40	240	200	160	4
42DF35A*	50	300	250	200	3
42EF35A*	60	360	300	240	3

### Class 42: 2 and 3 Pole 75-100 Amp Contactors




FEATURES

- Compact size
- Interchangeable mounting
- Straight thru wiring
- Encapsulated coils in a moisture proof epoxy
- Meets ARI-780, UL and CSA standards

Order No.	FLA	240V LRA	480V LRA	600V LRA	Poles
42FE15A*106	75	450	375	300	2
42FE35A*106	75	450	375	300	3
42GE15A*106	90	540	450	360	2
42GE35A*106	90	540	450	360	3
42HF35A*106	120	720	600	480	3
42IF35A*106	150	900	750	600	3

### Class 45: 1 and 2 Pole 20-40 Amp Contactors



FEATURES

- Compact size
- Interchangeable mounting
- Straight thru wiring
- Sems screws available on 25A, 30A and 40 A
- Binding Head Screws option on 40 A
- Class H Coil Insulation on 25-60 amp
- Meets ARI-780, UL and CSA Standards

Order No.	FLA	240V LRA	480V LRA	600V LRA	Poles
45CG20A*	20	120	100	80	2
45EG20A*	30	180	135	110	2
45FG20A*	35	200	135	110	2
45GG20A*	40	200	135	110	2

FURNAS CONTACTORS

