ZB38KCE-TFD

HCFC, R-22, 60Hz, 3- Phase, 460 V High Temp

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Accessories

Category	<u>PartNumber</u>	<u>Description</u>
Crankcase Heaters	018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length
	018-0095-01	Crankcase Heater, 480V, 70W, 21" Lead Length
	018-0095-02	Crankcase Heater, 575V, 70W, 21" Lead Length
	018-0095-03	Crankcase Heater, 240V, 70W, 32" Lead Length
	018-0095-04	Crankcase Heater, 240V, 70W, 48" Lead Length
	018-0095-05	Crankcase Heater, 480V, 70W, 48" Lead Length
	018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length
	018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length
	018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length
	018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length
	918-0043-00	Crankcase Heater Kit, 240V, 70W, Wrap Around, 48" Lead Length
	918-0043-01	Crankcase Heater Kit, 480V, 70W, Wrap Around, 48" Lead Length
	918-0043-02	Crankcase Heater Kit, 575V, 70W, Wrap Around, 48" Lead Length
	918-0043-07	Crankcase Heater Kit, 120V, 70W, Wrap Around, 48" Lead Length
	998-7024-00	Crankcase Heater Enclosure Box
Discharge Line	998-0166-00	Topcap Thermistor Kit
	998-0540-00	Discharge Line Thermostat Kit, 1/2" DLT-Stat 12" Leads, 2-Wire
	998-0540-02	Discharge Line Thermostat Kit, 1/2" DLT-Stat 36" Leads, 2-Wire
	998-0548-00	Discharge Line Thermostat Kit, 1/2" DLT-Stat 36" Leads With Alarm
	998-0548-01	Discharge Line Thermostat Kit, 3/4" DLT-Stat 36" Leads With Alarm
	998-7022-02	Discharge Line Thermostat Kit, 1/2", 36" Leads (Conduit Ready)
	998-7022-04	Discharge Line Thermostat Kit, 5/8", 36" Leads (Conduit Ready)

Matthew Meier 03/21/2018

Category	<u>PartNumber</u>	<u>Description</u>
	998-7022-07	Discharge Line Thermostat Kit, 3/4", 36" Leads (Conduit Ready)
Electrical	085-0160-00	3 Phase Voltage Monitor. For use with all Copeland 3 Phase Compressors. Consult model family nomenclature for electrical definition in the model number.
Miscellaneous	085-CP2M-7K	Dual High and Low Pressure Cut-Out Control
	998-E022-01	Polyol Ester Oil. Approved for use with specific Copeland Hermetic & Semi Hermetic models. Consult specific model family nomenclatures for oil identifier in the model number.
Mounting	527-0116-00	Spacer Mounting Kit, 30-35 Durometer, 1.45" OD, 0.44" ID, 0.75" Height
	527-0157-00	High Durometer Mount Kit, 60-70 Durometer, 1.62" OD, 0.44" ID, 1.16" Height
	527-0158-00	Hard Mount Kit, 1.42" OD, 0.34" ID, 0.92" Height
Oil Management	65365	Oil Management Control w/ Junction Box 24V, 50/60Hz
	65366	Oil Management Control w/ Series Relief Connector 24V, 50/60Hz
	65668	Oil Management, OMB Adapter (3/4" NPT)
	66650	Oil Management, OMB Adapter (1 1/4"-12 Rotalock)
Service Valves and	998-0034-02	Stub Tube to Rotalock, 7/8" Sweat to 1 1/4"-12 Thread
	998-0034-07	Rotalock to Stub Tube Adapter, 1 1/4"-12 Thread to 3/4" Sweat
	998-0034-08	Rotalock to Stub Tube Adapter, 1 1/4"-12 Thread to 7/8" Sweat
	998-0034-09	Rotalock to Stub Tube Adapter, 1 1/4"-12 Thread to 1 1/8" Sweat
	998-0034-15	Stub Tube to Rotalock, 1/2" Sweat (OD Applied) to 1"-14 Thread
	998-0034-17	Rotalock to Stub Tube Adapter, 1"-14 Thread to 5/8" Sweat
	998-0034-18	Rotalock to Stub Tube Adapter, 1"-14 Thread to 1/2" Sweat
	998-0069-00	Stub Tube to Rotalock, 7/8" Sweat to 1 1/4"-12 Thread and 1/2" Sweat to 1"-14 Thread
	998-0510-39	Service Valve Kit, 1 1/4"-12 Thread to 7/8" Sweat
	998-0510-41	Service Valve Kit, 1"-14 Thread to 5/8" Sweat
	998-0510-69	Service Valve Kit, 1 1/4"-12 Thread to 5/8" Sweat
	998-0510-89	Service Valve Kit, 1"-14 Thread to 7/8" Sweat
	998-0510-90	Service Valve Kit, 1 1/4"-12 Thread to 7/8" Sweat
	998-0510-98	Service Valve Kit, 1"-14 Thread to 1/2" Sweat
	998-5100-48	Service Valve Kit, 1 1/4"-12 Thread to 7/8" Sweat and 1"-14 Thread to 1/2" Sweat

<u>Category</u>	<u>PartNumber</u>	<u>Description</u>
	998-5100-61	Service Valve Kit, 1 1/4"-12 Thread to 7/8" Sweat and 1 1/4"-12 Thread to 5/8" Sweat
	998-5100-62	Service Valve Kit, 1 1/4"-12 Thread to 7/8" Sweat and 1 1/4"-12 Thread to 3/4" Sweat