



# LG 2018 Duct Free System Lineup

**Featuring LGRED®**  
POWERFUL HEAT TECHNOLOGY  
Reliable to Extreme Degrees

**Stroh Sales Associates, LLC**  
WWW.STROHSALES.COM • TEL: 610-933-6400




















LG System		Model	Category	SEER/EER/HSPF (Energy Star®) 18/12.5/9.6	AHRI Ref #	Lineset Liquid x Gas	Lineset Max Lgth/Max Elevation (ft)	Min Lineset Lgth (ft)	Pre-Charge (ft)/ Trim Charge (oz/ft)	Voltage MCA/MOP	Drain Pan Heater (ODU)	Smart ThinQ WiFi Compatible PCRCUDT3	Standard Remote Control	Operating Temp Range C/H (ODU)	Low Ambient Wind Baffle (ODU)	Capacity Range Btuh Cooling Heating	Rated Capacity C/H @ 95°/47°F	Max Heat Btuh @ 17°/5°F	MSRP \$	MSRP System Price \$
<b>PREMIER LGRED® HIGHEST EFFICIENCY &amp; HIGH HEAT OUTPUT (Single Zone) BEST</b>		LAN090HYV1	Indoor	27.5/15.65/12.0	7947563	1/4 x 3/8	65.6/32.8	6.6	41	208-230	Factory Installed	Yes	14°F-118°F / -13°F-65°F	Yes 0°F	1,023-12,966	9,000	11,940	\$651	\$2,037	
		LAU090HYV1	Outdoor	(ES)										11,000	11,220	\$1,386				
		LAN120HYV1	Indoor	25.5/13.8/12.0	7849625	1/4 x 3/8	65.6/32.8	6.6	41	208-230	Factory Installed	Yes		Yes 0°F	1,023-13,785	11,000	14,650	\$712	\$2,223	
		LAU120HYV1	Outdoor	(ES)										12,000	13,720	\$1,511				
		LAN150HYV2	Indoor	24/13.48/12.5	9680935	3/8 x 5/8	98.4/65.6	9.8	24.6	208-230	Factory Installed	Yes		Yes 0°F	3,070-21,000	15,000	21,430	\$882	\$2,394	
		LAU150HYV2	Outdoor	(ES)										18,000	18,950	\$1,512				
LAN180HYV2	Indoor	22/12.50/12.0	9680934	3/8 x 5/8	98.4/65.6	9.8	24.6	208-230	Factory Installed	Yes	Yes 0°F	3,070-29,515	18,200	27,400	\$1,061	\$2,762				
LAU180HYV2	Outdoor	(ES)									22,000	24,360	\$1,701							
LAN240HYV1	Indoor	22/12.5/12.0	8584526	3/8 x 5/8	98.4/65.6	9.8	24.6	208-230	Factory Installed	Yes	Yes 0°F	3,070-30,000	22,000	27,410	\$915	\$2,904				
LAU240HYV1	Outdoor	(ES)									27,000	23,690	\$1,989							
<b>ART COOL MIRROR Wall-Mount (Single Zone) BETTER</b>		LAN090HSV5	Indoor	23.5/14.5/11.3	10567393	1/4 x 3/8	82/49.2	6.6	41	208-230	Factory Installed	Yes Built In	14°F-118°F / -4°F-65°F	Yes 0°F	1,023-12,625	9,000	11,080	\$706	\$1,959	
		LSU090HSV5	Outdoor	(ES)										10,900	9,570	\$1,253				
		LAN120HSV5	Indoor	22.7/12.5/11.4	10570122	1/4 x 3/8	82/49.2	6.6	41	208-230	Factory Installed	Yes Built In		Yes 0°F	1,023-13,785	12,000	13,500	\$829	\$2,103	
		LSU120HSV5	Outdoor	(ES)										13,600	11,930	\$1,274				
LAN180HSV5	Indoor	21.5/12.6/10.2	10567390	3/8 x 5/8	114.8/49.2	9.8	24.6	208-230	Optional PQSH1200	Yes Built In	Yes 0°F	3,070-29,515	18,000	22,340	\$944	\$2,948				
LSU180HSV5	Outdoor	(ES)									21,600	19,300	\$2,004							
LAN240HSV3	Indoor	20.0/10.8/10.2	8797147	3/8 x 5/8	98.4/49.2	9.8	24.6	208-230	Optional PQSH1200	No	Yes 0°F	3,070-30,030	22,000	28,020	\$961	\$2,925				
LAU240HSV3	Outdoor	(ES)									27,600	24,220	\$1,964							
<b>HIGH EFFICIENCY Standard Wall-Mount (Single Zone) BETTER</b>		LSN090HSV5	Indoor	23.5/14.5/11.3	10567394	1/4 x 3/8	82/49.2	6.6	41	208-230	Factory Installed	Yes Built In	14°F-118°F/ -4°F-65°F	Yes 0°F	1,023-12,625	9,000	11,080	\$664	\$1,917	
		LSU090HSV5	Outdoor	(ES)										10,900	9,570	\$1,253				
		LSN120HSV5	Indoor	22.7/12.5/11.4	10570123	1/4 x 3/8	82/49.2	6.6	41	208-230	Factory Installed	Yes Built In		Yes 0°F	1,023-13,785	12,000	13,500	\$702	\$1,976	
		LSU120HSV5	Outdoor	(ES)										13,600	11,930	\$1,274				
		LSN180HSV5	Indoor	21.5/12.6/10.2	10567391	3/8 x 5/8	114.8/49.2	9.8	24.6	208-230	Optional PQSH1200	Yes Built In		Yes 0°F	3,070-29,515	18,000	22,340	\$1,004	\$3,008	
		LSU180HSV5	Outdoor	(ES)										21,600	19,300	\$2,004				
LSN243HLV	Indoor	21.5/12.5/11.0	9122552	3/8 x 5/8	164.0/98.4	9.8	24.6	208-230	No	Yes Built In	Yes 0°F	3,070-29,515	22,000	27,410	\$1,083	\$2,909				
LSU243HLV	Outdoor	(ES)									27,000	23,690	\$1,826							
<b>EXTENDED PIPE Wall-Mount (Single Zone) BETTER</b>		LSN303HLV	Indoor	19.0/10.0/10.0	9910427	3/8 x 5/8	164.0/98.4	9.8	24.6	208-230	Optional PQSH1200	Yes Built In	14°F-118°F/ -4°F-65°F	Yes 0°F	3,070-34,000	30,000	32,490	\$1,056	\$3,031	
		LSU303HLV	Outdoor	(ES)										32,000	28,080	\$1,975				
		LSN363HLV	Indoor	17.5/8.18/10.0	9910428	3/8 x 5/8	164.0/98.4	9.8	24.6	208-230	Optional PQSH1200	Yes Built In		Yes 0°F	3,070-34,000	33,000	35,740	\$1,400	\$4,022	
LSU363HLV	Outdoor	(ES)	35,200	30,890										\$2,622						
<b>MEGA Wall-Mount (Single Zone) GOOD</b>		LSN090HEV1	Indoor	19.0/12.5/9.0	8032527	1/4 x 3/8	49.2/22.9	9.8	24.6	208-230	No	No		14°F-118°F/ 14°F-65°F	No	3,070-9,500	8,500	9,140	\$429	\$1,229
		LSU090HEV1	Outdoor	(ES)											9,000	NA	\$800			
		LSN120HEV1	Indoor	17.0/10.5/8.5	8032528	1/4 x 3/8	49.2/22.9	9.8	24.6	208-230	No	No	No		3,070-13,780	12,000	12,180	\$460	\$1,316	
		LSU120HEV1	Outdoor	(ES)									12,000		NA	\$856				
		LSN180HEV1	Indoor	18.0/11/8.7	8046946	1/4 x 1/2	65.6/32.8	9.8	24.6	208-230	No	No	No		3,685-18,493	17,000	19,290	\$757	\$2,165	
		LSU180HEV1	Outdoor	(ES)									19,000		NA	\$1,408				
LSN240HEV1	Indoor	17.0/10.8/8.5	8046947	1/4 x 5/8	65.6/32.8	9.8	24.6	208-230	No	No	No	3,685-24,000	22,000	22,340	\$798	\$2,280				
LSU240HEV1	Outdoor	(ES)									22,000	NA	\$1,482							
<b>MEGA 115V (Single Zone)</b>		LSN090HXV	Indoor	17.0/12.0/9.0	7065151	1/4 x 3/8	49.2/23	6.6	24.6	115	No	No	14°F-118°F/ 14°F-65°F	No	1,023-13,785	8,500	11,070	\$429	\$1,229	
		LSU090HXV	Outdoor	(ES)										10,900	NA	\$800				
LSN120HXV	Indoor	17.0/10.5/9.0	7065150	1/4 x 3/8	49.2/23	6.6	24.6	115	No	No	No	1,023-13,785		12,000	13,200	\$460	\$1,316			
LSU120HXV	Outdoor	(ES)									13,000	NA		\$856						










LG DFS product & support information can be found at: [www.lg-dfs.com](http://www.lg-dfs.com) • Visit the LG Home Comfort Solutions site at: [www.lghomecomfort.com](http://www.lghomecomfort.com)






Warranty registration can be found at: [www.lg.com](http://www.lg.com) • Extended warranty information can be found at: [www.lg-dfs-warranty.com](http://www.lg-dfs-warranty.com)















LG Tech Support: (888)-865-3026, Option 2 • ALWAYS GET LG CASE (CNN) #

LG System		Model	Category	SEER/EER/HSPF (Energy Star®) 18/12.5/9.6	AHRI Ref #	Lineset Liquid x Gas	Lineset Max Lgth/Max Elevation (ft)	Min Lineset Lgth (ft)	Pre-Charge (ft)/ Trim Charge (oz/ft)	Voltage MCA/MOP	Drain Pan Heater (ODU)	Smart ThinQ WiFi Compatible PCRCUDT3	Standard Remote Control	Operating Temp Range C/H (ODU)	Low Ambient Wind Baffle (ODU)	Capacity Range Btuh Cooling Heating	Rated Capacity C/H @ 95°/47°F	Max Heat Btuh @ 17°/5°F	MSRP \$	MSRP System Price \$
Ceiling Cassette 28"x28" PT-UQC Grille is a Separate Accessory		LCN097HV4 LUU097HV	Indoor Outdoor	20.2/13.65/10.5 (ES)	8931560	1/4 x 3/8	66/49	6.6	25 0.22	208-230 11.9/15	No	No		0°F-118°F/ -4°F-64°F	Yes -4°F	3,600-9,900	9,000	9,350	\$759	\$2,604
		ZLABGP01A		4,400-12,100	11,000	8,250	\$1,845													
		Yes -4°F	3,400-12,400	11,100	11,900	\$919	\$2,926													
		ZLABGP01A		2,800-15,500	14,000	10,500		\$2,007												
		PT-UQC	27-9/16" x 27-9/16" Cassette Grille for LMCN***HV4																	\$139
PT-QCHWO	True 2'x2' 24-7/16" x 24-7/16" Cassette Grille for LMCN**HV4																	\$139		
PTDCQ	Decorative cover for 4-way cassette chassis requiring PT-UQC front grille																	\$239		
Ceiling Cassette 33"x33" PT-UMC1(B) Grille is a Separate Accessory		LCN187HV LUU187HV	Indoor Outdoor	20.0/15.0/10.1 (ES)	5859619	3/8 x 5/8	164 / 98.4	6.6	25 0.43	208-230 18.1/30	Optional PQSH1200	No		5°F-118°F / 0°F-64°F	Yes 0°F	9,500-19,800	18,000	14,330	\$1,700	\$4,250
		ZLABGP04A		9,300-22,000	20,000	11,271	\$2,550													
		Yes 0°F	9,700-26,700	24,000	21,343	\$1,800	\$4,750													
		ZLABGP04A		10,900-30,000	27,000	20,778		\$2,950												
		Yes 0°F 2X	14,000-42,000	36,000	30,311	\$2,450	\$6,075													
		ZLABGP04A		14,500-45,000	40,000	29,250		\$3,625												
		Yes 0°F 2X	17,100-47,100	42,000	34,681	\$2,775	\$6,925													
ZLABGP04A		17,100-52,600	47,000	33,351	\$4,150															
PT-UMC1	33"x33" White Cassette Grille Accessory for LCN**7HV Single Zone																	\$199		
PT-UMC1B	33"x33" Black Cassette Grille Accessory for LCN**7HV Single Zone																	\$234		
PTDCM	Decorative cover for 4-way cassette chassis requiring PT-UMC front grille																	\$329		
Low Static Ducted (Single Zone)		LDN097HV4 LUU097HV	Indoor Outdoor	18.5/12.7/10.3 (ES)	8931560	1/4 x 3/8	66/49	6.6	24.6 0.22	208-230 11.9/15	No	No		0°F-118°F/ -4°F-64°F	Yes -4°F	3,600-9,900	9,000	11,900	\$876	\$2,721
		ZLABGP01A		5,600-15,400	14,000	10,500	\$1,845													
High Static Ducted (Single Zone)		LDN127HV4 LUU127HV	Indoor Outdoor	19.6/12.9/10.5 (ES)	8905114	1/4 x 3/8	66/49	6.6	24.6 0.22	208-230 12.3/15	No	No		0°F-118°F/ -4°F-64°F	Yes -4°F	4,640-12,760	11,600	13,600	\$901	\$2,908
		ZLABGP01A		6,400-17,600	16,000	12,000	\$2,007													
4-Way Multi- Position Ducted (Single Zone) <b>NEW!</b>		LHN247HV LUU247HV	Indoor Outdoor	17.0/12.0/10.0	5859621	3/8 x 5/8	164 / 98.4	6.6	25 0.43	208-230 18.1/30	Optional PQSH1200	No		5°F-118°F / 0°F-64°F	Yes 0°F	9,700-26,700	24,000	20,257	\$1,275	\$4,225
		ZLABGP04A		10,900-30,000	27,000	19,556	\$2,950													
4-Way Multi- Position Ducted (Single Zone) <b>NEW!</b>		LHN367HV LUU367HV	Indoor Outdoor	17.6/12.1/9.2	5859622	3/8 x 5/8	246 / 98.4	6.6	25 0.43	208-230 21.4/40	Optional PQSH1200	No		5°F-118°F / -4°F-64°F	Yes 0°F 2X	16,000-41,400	36,000	32,332	\$2,150	\$5,775
		ZLABGP04A		17,500-48,000	40,000	31,200	\$3,625													
		Yes -4°F	8,000-24,000	18,000	18,000	\$2,320	\$4,503													
		ZLABGP04A		9,000-23,000	20,000	16,000		\$2,183												
		Yes -4°F	9,000-28,000	24,000	22,000	\$2,344	\$5,026													
ZLABGP04A		10,000-30,000	27,000	20,000	\$2,682															
Yes -4°F 2X	14,000-44,000	36,000	32,000	\$2,601	\$5,945															
ZLABGP04A		15,000-47,000	40,000	30,000		\$3,344														
Yes -4°F 2X	17,000-48,000	42,000	37,000	\$2,747	\$6,531															
ZLABGP04A		18,000-55,000	47,000	32,000		\$3,784														
Yes -4°F 2X	18,000-53,000	48,000	40,000	\$3,249	\$7,349															
ZLABGP04A		19,000-60,000	56,000	34,000		\$4,100														
<b>Accessories</b> Refer to individual system data sheets or IDU/ODU installation manuals for all available & compatible accessories	PSWMOZ3 LG SIMs 2.0 Diagnostic WiFi Module														\$99					
	PCRCUDT3 LG Smart AC WiFi Compatibility Module for Smartphone														\$99					
	PQSH1200 Drain Pan Heater for ODU (See ODU install manual for compatability)														\$225					
	PQSH1201 Drain Pan Heater for ODU (See ODU install manual for compatability)														\$168					
	ZLABGP01A Low Ambient Cooling Wind Baffle for ODU														\$124					
	ZLABGP02A Low Ambient Cooling Wind Baffle for ODU														\$127					
	ZLABGP03A Low Ambient Cooling Wind Baffle for ODU														\$113					
	ZLABGP04A Low Ambient Cooling Wind Baffle for ODU														\$120					
	PDRYCB300 Dry Contact for 3rd Part Thermostat (5-12Vdc, 24 Vac)														\$209					
	PREMTBVC0 MultiSITE Thermostat														\$315					
	PREMTBCV1 MultiSITE Thermostat (On-board Motion & Humidity Sensor)														\$340					
	PREMTB10U Programmable Thermostat w/ 2 Set Points (White)														\$179					
	PREMTA000 Programmable Premium Thermostat														\$355					
	PZCWRC1 32.8' Extension Cable for Wired Thermostat														\$19					
Hard Wired Controllers (Controllers DO NOT include 32.8' Extension Cable) All Current LG DFS Indoor Units (EXCEPT 208/230v MEGA) are compatible with Hard Wired Controllers																				

LG System		Model	Category	SEER/EER/HSPF (Energy Star®) 18/12.5/9.6	AHRI Ref #	Lineset Liquid x Gas	Lineset Max Lgth/Max Elevation (ft)	Min Lineset Lgth (ft)	Pre-Charge (ft)/ Trim Charge (oz/ft)	Voltage MCA/MOP	Drain Pan Heater (ODU)	Smart ThinQ WiFi Compatible PCRCUDT3	Standard Remote Control	Operating Temp Range C/H (ODU)	Low Ambient Wind Baffle (ODU)	Capacity Range Btuh Cool/Heat (Max Capacity Connectability)	Rated Capacity C/H @ 95°/47°F	Max Heat Btuh @ 17°/5°/-4°F	MSRP \$	MSRP Individual Price \$
Multi F ODU (Multi Zone)		LMU18CHV (Must Connect 2 IDU)	Non-Ducted IDU	22.0/13.0/9.7 (ES)	7180060	1/4x3/8 (2)	Max ODU to IDU Piping 82'. Max Total Piping Lgth 164' / Max Elev between ODU & IDU 49.2'. Max Elev between IDU & IDU 24.6'.	9.8	49.2 .22	208-230 13.3/20	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F ZLABGP03A	8,400-19,000/ 10,248-24,000 (24,000)	17,000 22,000	19,161 14,807 9,912	\$1,943	\$1,943
			Ducted IDU	17.2/10.7/9.7	7180061												14,000 19,800	17,245 13,327 8,920		
			Mixed Ducted & Non-ducted IDU	19.6/11.8/9.7	7184506												15,500 20,9000	18,203 14,067 9,416		
		LMU24CHV (Connect 2-3 IDU)	Non-ducted IDU	21.7/13.5/10.6 (ES)	7180062	1/4x3/8 (3)	Max ODU to IDU Piping 82'. Max Total Piping Lgth 246.1' / Max Elev between ODU & IDU 49.2'. Max Elev between IDU & IDU 24.6'.	9.8	73.8 .22	208-230 14.3/20	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F ZLABGP03A	8,400-25,000/ 9,240-28,800 (33,000)	20,000 24,000	21,097 14,595 10,385	\$2,283	\$2,283
			Ducted IDU	17.5/11.5/9.8	7184505												17,800 22,400	19,691 13,623 9,693		
			Mixed Ducted & Non-ducted IDU	19.6/12.5/10.2 (ES)	7184507												18,900 23,200	20,394 14,109 10,039		
		LMU30CHV (Connect 2-4 IDU)	Non-Ducted IDU	22.0/13.0/10.0 (ES)	8111355	1/4x3/8 (4)	Max ODU to IDU Piping 82'. Max Total Piping Lgth 246.1' / Max Elev between ODU & IDU 49.2'. Max Elev between IDU & IDU 24.6'.	9.8	98.4 .22	208-230 16.6/25	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F ZLABGP04A	8,400-36,000/ 9,240-38,400 (40,000)	30,000 32,000	26,739 20,622 13,753	\$2,872	\$2,872
			Ducted IDU	18.2/11.0/9.7	8111356												27,400 33,000	24,817 19,140 12,765		
			Mixed Ducted & Non-Ducted IDU	20.1/12.0/9.85	8111359												28,700 32,500	25,778 19,881 13,259		
		LMU36CHV (Connect 2-4 IDU)	Non-Ducted IDU	22.0/13.0/10.0 (ES)	7180063	1/4x3/8 (4)	Max ODU to IDU Piping 82'. Max Total Piping Lgth 246.1' / Max Elev between ODU & IDU 49.2'. Max Elev between IDU & IDU 24.6'.	9.8	98.4 .22	208-230 17.9/25	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F ZLABGP04A	8,400-38,400/ 9,240-41,600 (48,000)	32,000 36,000	29,105 22,057 15,823	\$3,460	\$3,460
			Ducted IDU	18.2/11.0/9.7	7180064												28,000 34,000	27,489 20,831 14,945		
			Mixed Ducted & Non-ducted IDU	20.1/12.0/9.9	7184508												30,000 35,000	28,297 21,444 15,384		

LG System		Model	Category	SEER/EER/HSPF (Energy Star®) 18/12.5/9.6	AHRI Ref #	Lineset Liquid x Gas	Lineset Max Lgth/Max Elevation (ft)	Min Lineset Lgth (ft)	Pre-Charge (ft)/ Trim Charge (oz/ft)	Voltage MCA/MOP	Drain Pan Heater (ODU)	Smart ThinQ WiFi Compatible PCRCUDT3	Standard Remote Control	Operating Temp Range C/H (ODU)	Low Ambient Wind Baffle (ODU)	Capacity Range Btuh Cool/Heat (Max Capacity Connectability)	Rated Capacity C/H @ 95°/47°F	Max Heat Btuh @ 17°/5°/-4°F	MSRP \$	MSRP Individual Price \$
Multi F Max ODU (Multi Zone)		LMU480HV PMBD Unit(s) Required (Connect 2-8 IDU with minimum capacity of 20,000 btuhs)	Non-ducted IDU	19.35/12.5/10.0 (ES)	8111358	3/8x3/4 PMBD Unit(s) Required	Max ODU to IDU Piping 229.6'. Max Total Piping Lgth 475.7' / Max Elev between ODU & IDU 98.4' . IDU & IDU 49.2'.	9.8	Main: 16.4 Branch: 131.2 / Main: .54 Branch: .22	208-230 27.3/40	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F 2x ZLABGP04A	14,400-58,000/ 15,840-61,000 (65,000)	48,000 54,000	49,014 38,900 27,529	\$3,702	\$3,702
		Ducted IDU	17.5/10.8/9.7	8111357	44,000 50,000												45,382 36,018 25,491			
		Mixed Ducted & Non-ducted IDU	18.5/11.6/9.9	8111360	46,000 52,000												47,198 37,459 26,510			
		LMU540HV PMBD Unit(s) Required (Connect 2-8 IDU with minimum of 22,000 btuhs)	Non-ducted IDU	18.40/10.3/8.7	5589698	3/8x3/4 PMBD Unit(s) Required	Max ODU to IDU Piping 229.6'. Max Total Piping Lgth 475.7' / Max Elev between ODU & IDU 98.4' . IDU & IDU 49.2'.	9.8	Main: 16.4 Branch: 131.2 / Main: .54 Branch: .22	208-230 24.8/40	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F 2X ZLABGP04A	14,400-63,200/ 16,272-64,000 (73,000)	52,500 58,000	51,832 41,137 29,112	\$4,075	\$4,075
		Ducted IDU	15.8/10.0/8.3	5589996	51,000 58,000												51,832 41,137 29,112			
		Mixed Ducted & Non-ducted IDU	17.1/10.2/8.5	5589997	51,7500 58,000												51,832 41,137 29,112			
		LMU600HV PMBD Unit(s) Required (Connect 2-8 IDU with minimum of 24,000 btuhs)	Non-ducted IDU	20.5/11.4/11.0	8898928	3/8x3/4 PMBD Unit(s) Required	Max ODU to IDU Piping 229.6'. Max Total Piping Lgth 475.7' / Max Elev between ODU & IDU 98.4' . IDU & IDU 49.2'.	9.8	Main: 16.4 Branch: 131.2 / Main: .54 Branch: .22	208-230 32.2/45	Optional PQSH1200	NA	NA	Cooling: 14°F-118°F (-4° with wind baffle)/ Heating: -4°F-64°F	Yes -4°F 2x ZLABGP04A	15,600-68,000/ 17,940-70,000 (81,000)	60,000 64,000	53,560 42,720 33,193	\$5,089	\$5,089
		Ducted IDU	18.5/10.5/10.5	8898929	58,000 64,000												53,982 43,496 34,613			
		Mixed Ducted & Non-ducted IDU	19.5/10.94/10.8	8898930	59,000 64,000												53,771 43,108 33,903			

LG System		Model	Category	Number of Ports	Lineset Liquid x Gas	Lineset Max Lgth/Max Elevation (ft)	Min Lineset Lgth (ft)	Pre-Charge (ft)/ Trim Charge (oz/ft)	Voltage	Smart ThinQ WiFi Compatible PCRCUDT3	Standard Remote Control	Operating Temp Range C/H	Low Ambient Wind Baffle (ODU)	Max Capacity Connectibility	MSRP \$	MSRP Individual Price \$			
Branch Distribution (BD) Units for Multi F Max		PMBD3620	At least one BD Unit Required for Use With Multi F Max LMU480HV, LMU540HV, LMU600HV, LMU360HHV or LMU420HHV (PMBL5620 Y- Branch Connector is a <i>Required</i> Accessory if using more than one BD Unit)	1-2	1/4x3/8 (2)	Max ODU to BD(s):180.4'. Max BD to each IDU: 49.2'. Max Total BD(s) to IDU(s): 295.3'. Elev between BD & IDU: 32.8'; BD & BD: 49.2'.	10' from ODU to PMBD or from PMBD to IDU. 3' from ODU to Y & 2' from Y to PMBD.		208-230	NA	NA	0° to 150° F	N/A	48,000 Max Connected Capacity	\$400	\$400			
		PMBD3630		1-3	1/4x3/8 (3)									72,000 Max Connected Capacity			Maximum nominal capacity per port A,B & C is 24,000 Btuh	\$425	\$425
		PMBD3640		1-4	1/4x3/8 (4)									73,000 Max Connected Capacity				\$550	\$550
		PMBD3641 (Required for LM*N360HV)		1-4	1/4x3/8(3) + 1/4x1/2(1)									73,000 Max Connected Capacity				Maximum nominal capacity for port D is 36,000 Btuh	\$575
		PMBL5620	Y-Branch Connector for Multi F Max LMU480/540/600HV	NA	3/8x3/4									2 x PMBD36**	\$180	\$180			

LG System		Model	Category	Compatible with Multi F ODU LMU**0(C,H)HV	Lineset Liquid x Gas	Lineset Max Lgth/Max Elevation (ft)	Min Lineset Lgth (ft)	Pre-Charge (ft)/ Trim Charge (oz/ft)	Voltage	Capacity for Connecting to ODU	Smart ThinQ WiFi Compatible PCRCUDT3	Standard Remote Control	Additional Information (Please see installation manuals for all installation requirements)	MSRP \$	MSRP Individual Price \$		
Multi F IDU (Multi Zone)		LMN078HVT	Standard Wall Mount	18,24,30,36,42,48,54,60	1/4 x 3/8	For LMU18, 24, 30 & 36: Max Lgth not to exceed 82' per IDU. Elev between ODU & IDU 49.2' / IDU & IDU 24.6'. For LMU48 & 54: Max Lgth not exceed 49.2' from BD to IDU. Elev between BD & IDU: 32.8' / IDU & IDU: 49.2'. Always refer to install manual.	10' from ODU to IDU or from PMBD to IDU		208-230	7,000	Yes For Models Produced after 11/2015		For lineset sizes other than 1/4 x 3/8, required pipe adapters will be included in IDU package. Always verify proper lineset size for all Multi F systems.	\$606	\$606		
		LSN090HSV5		18,24,30,36,42,48,54,60	1/4 x 3/8					9,000				\$615	\$664		
		LSN120HSV5		18,24,30,36,42,48,54,60	1/4 x 3/8					12,000				\$650	\$702		
		LMN158HVT		18,24,30,36,42,48,54,60	1/4 x 3/8					15,000				\$895	\$895		
		LSN180HSV5		24,30,36,42,48,54,60	1/4 x 1/2					18,000				\$930	\$1,004		
		LMN248HVT		24,30,36,42,48,54,60	1/4 x 1/2					24,000				\$1,269	\$1,269		
		LAN090HSV5	Mirror Wall Mount	18,24,30,36,42,48,54,60	1/4 x 3/8					9,000	Yes			\$654	\$706		
		LAN120HSV5		18,24,30,36,42,48,54,60	1/4 x 3/8					12,000				\$768	\$829		
		LAN180HSV5		24,30,36,42,48,54,60	1/4 x 1/2					18,000				\$874	\$944		
		LMAN097HVP	Gallery	18,24,30,36,42,48,54,60	1/4 x 3/8					9,000	No			\$861	\$861		
		LMAN127HVP	Wall Mount	18,24,30,36,42,48,54,60	1/4 x 3/8					11,200				\$950	\$950		
		LDN097HV4	Low Static Ducted	18,24,30,36,42,48,54,60	1/4 x 3/8					9,000	No			\$876	\$876		
		LDN127HV4		18,24,30,36,42,48,54,60	1/4 x 3/8					12,000				\$901	\$901		
		LMDN186HV		30,36,42,48,54,60	1/4 x 1/2					18,000				\$1,176	\$1,176		
		LMHN240HV	High Static	30,36,42,48,54,60	1/4 x 1/2					24000*	No			\$1,300	\$1,300		
		LMHN360HV	Ducted	42,48,54,60 + PMBD3641	3/8 x 5/8					36000*				\$1,800	\$1,800		
		LVN180HV4	Multi Position Ducted	24,30,36,42,48,54,60	1/4 x 1/2					18,000	Yes			\$2,183	\$2,183		
		LVN240HV4		30,36,42,48,54,60	3/8 x 5/8					24000*				\$2,344	\$2,344		
		LVN360HV4		42,48,54,60 + PMBD3641	3/8 x 5/8					36000*				\$2,601	\$2,601		
		ANEH053B1	5 Kw Electric Heater Kit for LVN**0HV4								*Multiply capacity by 1.3	NA		NA	PREMT**** Controller is required if using optional electric heater kit. Heat Kits available in 3,5,8,10, 15 & 20 kW	\$163	\$163
		ANEH103B2	10 Kw Electric Heater Kit for LVN**0HV4								\$265				\$265		
		PREMTBCV1	MultiSITE Thermostat (Motion & Humidity Sensor)								\$340				\$340		
	PREMTB10U	Programmable Thermostat w/ 2 Set Points (White)								\$179	\$179						
		LMCN077HV	Ceiling Cassette	18,24,30,36,42,48,54,60	1/4 x 3/8					7,000	No			Standard Ceiling Cassette Grille PT-UQC or Optional True 2'x2' Ceiling Cassette Grille PT-QCHW0 must be ordered separately	\$583	\$583	
		LCN097HV4		18,24,30,36,42,48,54,60	1/4 x 3/8					9,000				\$759	\$759		
		LCN127HV4		18,24,30,36,42,48,54,60	1/4 x 3/8					12,000				\$919	\$919		
		LMCN185HV		24,30,36,42,48,54,60	1/4 x 1/2					18,000				\$1,297	\$1,297		
		PT-UQC		Cassette Grille for LMCN***HV4										\$139	\$139		
PT-QCHW0		True 2'x2' Cassette Grille for LMCN***HV4				\$139	\$139										