

# CR24K6E-PFV

HFC, R-407C, 60Hz, 1- Phase, 208/230 V

Air Conditioning



**Production Status:** Preliminary data only - Contact your Emerson Climate Technologies Representative.

## Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	22600	31500
Power (Watts):	2140	1765
Current (Amps):	9.50	8.10
EER (Btu/Wh):	10.55	17.80
Mass Flow (lbs/hr):	329	391
Sound Power (dBA):	72 Avg	77 Max
Vibration (mils(peak-peak)):	2.3 Avg	3.3 Max
Record Date:	2009-09-25	

## Mechanical

Number of Cylinders:	2	Displ(in <sup>3</sup> /Rev):	2.70
Bore Size(in):	1.66	Displ(ft <sup>3</sup> /hr):	328.22
Stroke(in):	0.63		
Overall Length (in):	10.23	Mounting Length (in):	7.50
Overall Width (in):	9.65	Mounting Width (in):	7.50
Overall Height (in):	13.44	Mounting Height (in):	13.81 *
Suction Size (in):	3/4 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	43		
Initial Oil Charge (oz):	45		
Net Weight (lbs):	63		
Internal Free Volume (in <sup>3</sup> ):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	61.0	MCC (Amps):	17.4	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	28-Dec-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		12.4			
RLA(=MCC/1.56;use for breaker & wire size selection):		11.2			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-16	43.0	52.0	330	LOW TORQUE
Start Capacitor	014-0061-28	145.0	175.0	250	HIGH TORQUE
Run Capacitor	014-0064-07	35.0	0.0	370	

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	1	200	UL High Temp
R-407C HFC	50	1	200	UL High Temp
R-22 HCFC	60	1	208/230	
R-407C HFC	50	1	200	Air Conditioning