

CS10K6E-TF5

HFC, R-404A, 60Hz, 3- Phase, 200/230 V

Extended Medium Temp



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	20 / 120	-10 / 120
RG(°F)/Liq(°F)	40.0 / 120.0	40.0 / 120.0
Capacity (Btu/hr)	9940	3010
Power (Watts):	1610	926
Current (Amps):	5.20	3.30
EER (Btu/Wh):	6.20	3.20
Mass Flow (lbs/hr):	238	69
Sound Power (dBA):	0 Avg	0 Max
Vibration (mils(peak-peak)):	0.0 Avg	0.0 Max
Record Date:	2002-04-29	

Mechanical

Number of Cylinders:	2	Displ(in^3/Rev):	2.26
Bore Size(in):	1.52	Displ(ft^3/hr):	275.07
Stroke(in):	0.63		
Overall Length (in):	10.28	Mounting Length (in):	7.50
Overall Width (in):	9.09	Mounting Width (in):	7.50
Overall Height (in):	14.31	Mounting Height (in):	14.69 *
Suction Size (in):	5/8 Stub		
Discharge Size (in):	1/2 Stub		
Oil Recharge (oz):	43		
Initial Oil Charge (oz):	45		
Net Weight (lbs):	71		
Internal Free Volume (in^3):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	51.0	MCC (Amps):	10.5	UL File No:	
LRA-Half Winding:		RPM:	3500	UL File Date:	28-Dec-1984
LRA Low*:		Max Operating Current:	9.0		
RLA(=MCC/1.4;use for contactor selection):	7.5				
RLA(=MCC/1.56;use for breaker & wire size selection):	6.7				
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	60	3	200/230	Medium Temperature
R-134a HFC	60	3	200/230	High Temp
R-404A HFC	60	3	200/230	High Temp
R-507 HFC	60	3	200/230	Extended Medium Temp
R-507 HFC	60	3	200/230	