

KAKB-021A-CAV

HCFC, R-22, 60Hz, 1- Phase, 208/230 V

Low Temperature



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	-25 / 105	-40 / 105
RG(°F)/Liq(°F)	65.0 / 105.0	65.0 / 105.0
Capacity (Btu/hr)	4030	2340
Power (Watts):	1090	910
Current (Amps):	5.90	5.30
EER (Btu/Wh):	3.70	2.60
Mass Flow (lbs/hr):	54	31
Sound Power (dBA):		
Vibration (mils(peak-peak)):		4.76 Max
Record Date:	2007-01-03	

Mechanical

Number of Cylinders:	2	Displ(in ³ /Rev):	4.20
Bore Size(in):	1.69	Displ(ft ³ /hr):	255.09
Stroke(in):	0.94		
Overall Length (in):	14.38	Mounting Length (in):	8.19
Overall Width (in):	9.50	Mounting Width (in):	6.38
Overall Height (in):	10.44	Mounting Height (in):	11.19 *
Suction Size (in):		7/8 Sweat	
Discharge Size (in):		1/2 Flare	
Oil Recharge (oz):		20	
Initial Oil Charge (oz):		22	
Net Weight (lbs):		106	
Internal Free Volume (in ³):			
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	55.0	MCC (Amps):	12.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	23-Jul-1984
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		9.1			
RLA(=MCC/1.56;use for breaker & wire size selection):		8.2			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					
Type	Part No	Low MFD	High MFD	Volts	User Description
Start Capacitor	014-0061-30	130.0	156.0	330	
Run Capacitor	014-0064-14	40.0	0.0	440	

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-12 CFC	50	1	200/220	UL Medium Temp
R-22 HCFC	50	1	200/220	High Temp
R-22 HCFC	50	1	200/220	Low Temperature
R-22 HCFC	50	1	200/220	Medium Temperature
R-507 HFC	50	1	200/220	
R-12 CFC	60	1	208/230	UL Medium Temp
R-22 HCFC	60	1	208/230	High Temp
R-22 HCFC	60	1	208/230	Medium Temperature
R-507 HFC	60	1	208/230	