

6DN3R37ME-TSN

HCFC, R-22, 60Hz, 3- Phase, 230 V

Air Conditioning



Production Status: This compressor and/or application of this compressor is not available to U.S. OEM customers. A field replacement is currently available through a U.S. Emerson Climate Technologies Wholesaler. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	35 / 105
RG(°F)/Liq(°F)	65.0 / 115.0	55.0 / 90.0
Capacity (Btu/hr)	420000	406000
Power (Watts):	38900	30100
Current (Amps):	58.90	48.20
EER (Btu/Wh):	10.80	13.50
Mass Flow (lbs/hr):	6150	5400
Sound Power (dBA):		
Vibration (mils(peak-peak)):		3.17 Max
Record Date:	2007-06-12	

Mechanical

Number of Cylinders:	6	Displ(in ³ /Rev):	81.59
Bore Size(in):	2.81	Displ(ft ³ /hr):	4957.48
Stroke(in):	2.19		
Overall Length (in):	30.19	Mounting Length (in):	15.00
Overall Width (in):	22.44	Mounting Width (in):	12.00
Overall Height (in):	20.34	Mounting Height (in):	21.53 *
Suction Size (in):		2 1/8 Sweat	
Discharge Size (in):		1 5/8	
Oil Recharge (oz):		130	
Initial Oil Charge (oz):		140	
Net Weight (lbs):		550	
Internal Free Volume (in ³):			
Horse Power:		30	
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	594.0	MCC (Amps):	175.0	UL File No:	SA-2337
LRA-Half Winding:	340.0	RPM:	3500	UL File Date:	07-Apr-1971
LRA Low*:		Max Operating Current:			
RLA(=MCC/1.4;use for contactor selection):		125			
RLA(=MCC/1.56;use for breaker & wire size selection):		112.2			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-407F HFC	60	3	230	Air Conditioning
R-407A HFC	50	3	200	Air Conditioning
R-407A HFC	50	3	400	Air Conditioning
R-407C HFC	50	3	200	Air Conditioning
R-407C HFC	50	3	400	Air Conditioning
R-407C HFC	50	3	200	Medium Temp, Low Condensing
R-407C HFC	50	3	400	Medium Temp, Low Condensing
R-407C HFC	60	3	230	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	230	Medium Temp, Low Condensing

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-407C HFC	60	3	460	Medium Temp, Low Condensing
R-407A HFC	60	3	230	Air Conditioning
R-407F HFC	60	3	460	Air Conditioning
R-407A HFC	60	3	460	Medium Temp, Low Condensing
R-407A HFC	60	3	230	Medium Temp, Low Condensing
R-22 HCFC	50	3	200	Medium Temp, Low Condensing
R-22 HCFC	50	3	200	Air Conditioning
R-502 CFC	50	3	200	Medium Temperature
R-404A HFC	50	3	200	
R-404A HFC	50	3	200	Air Conditioning
R-507 HFC	50	3	200	
R-507 HFC	50	3	200	Air Conditioning
R-407C HFC	50	3	200	Air Conditioning
R-407C HFC	50	3	200	Medium Temp, Low Condensing
R-407A HFC	50	3	200	Air Conditioning
R-407A HFC	50	3	200	Medium Temp, Low Condensing
R-407F HFC	50	3	200	
R-407F HFC	50	3	200	Air Conditioning
R-448A HFO	50	3	200	Medium Temp, Low Condensing
R-448A HFO	50	3	200	
R-449A HFO	50	3	200	Medium Temp, Low Condensing
R-449A HFO	50	3	200	
R-22 HCFC	60	3	230	Medium Temp, Low Condensing
R-502 CFC	60	3	230	Medium Temperature
R-404A HFC	60	3	230	Medium Temp, Low Condensing
R-404A HFC	60	3	230	Air Conditioning
R-507 HFC	60	3	230	Medium Temp, Low Condensing
R-507 HFC	60	3	230	Air Conditioning
R-407C HFC	60	3	230	Air Conditioning
R-407C HFC	60	3	230	Medium Temp, Low Condensing
R-407A HFC	60	3	230	Air Conditioning
R-407A HFC	60	3	230	Medium Temp, Low Condensing
R-407F HFC	60	3	230	
R-407F HFC	60	3	230	Air Conditioning
R-448A HFO	60	3	230	Medium Temp, Low Condensing
R-448A HFO	60	3	230	
R-449A HFO	60	3	230	Medium Temp, Low Condensing
R-449A HFO	60	3	230	
R-22 HCFC	50	3	400	Medium Temp, Low Condensing
R-22 HCFC	50	3	400	Air Conditioning
R-502 CFC	50	3	400	Medium Temperature
R-404A HFC	50	3	400	
R-404A HFC	50	3	400	Air Conditioning

Alternate Applications

<u>Refrigerant</u>	<u>Freq (Hz)</u>	<u>Phase</u>	<u>Voltage</u>	<u>Application</u>
R-507 HFC	50	3	400	
R-507 HFC	50	3	400	Air Conditioning
R-407C HFC	50	3	400	Air Conditioning
R-407C HFC	50	3	400	Medium Temp, Low Condensing
R-407A HFC	50	3	400	Air Conditioning
R-407A HFC	50	3	400	Medium Temp, Low Condensing
R-407F HFC	50	3	400	
R-407F HFC	50	3	400	Air Conditioning
R-448A HFO	50	3	400	Medium Temp, Low Condensing
R-448A HFO	50	3	400	
R-449A HFO	50	3	400	Medium Temp, Low Condensing
R-449A HFO	50	3	400	
R-22 HCFC	60	3	460	Medium Temp, Low Condensing
R-22 HCFC	60	3	460	Air Conditioning
R-502 CFC	60	3	460	Medium Temperature
R-404A HFC	60	3	460	Medium Temp, Low Condensing
R-404A HFC	60	3	460	Air Conditioning
R-507 HFC	60	3	460	Medium Temp, Low Condensing
R-507 HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Air Conditioning
R-407C HFC	60	3	460	Medium Temp, Low Condensing
R-407A HFC	60	3	460	Air Conditioning
R-407A HFC	60	3	460	Medium Temp, Low Condensing
R-407F HFC	60	3	460	
R-407F HFC	60	3	460	Air Conditioning
R-448A HFO	60	3	460	Medium Temp, Low Condensing
R-448A HFO	60	3	460	
R-449A HFO	60	3	460	Medium Temp, Low Condensing
R-449A HFO	60	3	460	
R-407A HFC	50	3	400	Medium Temp, Low Condensing
R-407A HFC	50	3	200	Medium Temp, Low Condensing
R-407F HFC	50	3	200	Air Conditioning
R-407F HFC	50	3	400	Air Conditioning
R-407A HFC	60	3	460	Air Conditioning