

ZP49K5E-TF5

HFC, R-410A, 60Hz, 3- Phase, 200/230 V

Air Conditioning



Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance

Evap(°F)/Cond(°F)	45 / 130	50 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	70.0 / 85.0
Capacity (Btu/hr)	49700	66500
Power (Watts):	4650	3080
Current (Amps):	13.40	9.90
EER (Btu/Wh):	10.70	21.60
Mass Flow (lbs/hr):	731	816
Sound Power (dBA):	71 Avg	76 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	2012-12-10	

Mechanical

Number of Cylinders:	0	Displ(in ³ /Rev):	2.83
Bore Size(in):	0.00	Displ(ft ³ /hr):	344.05
Stroke(in):	0.00		
Overall Length (in):	9.56	Mounting Length (in):	7.50
Overall Width (in):	9.56	Mounting Width (in):	7.50
Overall Height (in):	16.94	Mounting Height (in):	17.17 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		38	
Initial Oil Charge (oz):		42	
Net Weight (lbs):		72	
Internal Free Volume (in ³):		190.8	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

Electrical

LRA-High*:	110	MCC (Amps):	24.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	17-Dec-2003
LRA Low*:		Max Operating Current:	20.0		
RLA(=MCC/1.4;use for contactor selection):		17.7			
RLA(=MCC/1.56;use for breaker & wire size selection):		15.9			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-410A HFC	50	3	200/220	Air Conditioning