

# ZR57K3-TFD

HCFC, R-22, 60Hz, 3- Phase, 460 V  
Air Conditioning



**Production Status:** Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Performance

Evap(°F)/Cond(°F)	45 / 130	45 / 100
RG(°F)/Liq(°F)	65.0 / 115.0	65.0 / 85.0
Capacity (Btu/hr)	58500	68500
Power (Watts):	5000	3440
Current (Amps):	7.30	5.50
EER (Btu/Wh):	11.70	19.90
Mass Flow (lbs/hr):	860	880
Sound Power (dBA):	74 Avg	79 Max
Vibration (mils(peak-peak)):	2.0 Avg	3.0 Max
Record Date:	1993-06-18	

## Mechanical

Number of Cylinders:	0	Displ(in <sup>3</sup> /Rev):	4.71
Bore Size(in):	0.00	Displ(ft <sup>3</sup> /hr):	572.40
Stroke(in):	0.00		
Overall Length (in):	9.69	Mounting Length (in):	7.50
Overall Width (in):	9.69	Mounting Width (in):	7.50
Overall Height (in):	17.24	Mounting Height (in):	17.99 *
Suction Size (in):		7/8 Stub	
Discharge Size (in):		1/2 Stub	
Oil Recharge (oz):		62	
Initial Oil Charge (oz):		66	
Net Weight (lbs):		85	
Internal Free Volume (in <sup>3</sup> ):		257.0	
Horse Power:			
*Overall compressor height on Copeland Brand Product's specified mounting grommets.			

## Electrical

LRA-High*:	62.0	MCC (Amps):	12.8	UL File No:	SA-2337
LRA-Half Winding:		RPM:	3500	UL File Date:	26-Jul-1993
LRA Low*:		Max Operating Current:	11.0		
RLA(=MCC/1.4;use for contactor selection):		9.1			
RLA(=MCC/1.56;use for breaker & wire size selection):		8.2			
*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.					

## Alternate Applications

Refrigerant	Freq (Hz)	Phase	Voltage	Application
R-22 HCFC	50	3	380/420	Air Conditioning