

DuPont Refrigerants

U.S. GENERAL REPLACEMENT GUIDE

RECOMMENDED R-22 REPLACEMENTS*

<p>ISCEON® MO99™ R-438A</p> <p>HFC Retrofit</p> <p>Lubricant MO AB POE</p> <p>Evaporator Temp High Medium Low</p> <p>Applications AC: Commercial Lt Commercial Refrigeration: Commercial Industrial</p>	<p>ISCEON® MO29 R-422D</p> <p>HFC Retrofit</p> <p>Lubricant MO AB POE</p> <p>Evaporator Temp Medium Low</p> <p>Applications Refrigeration: Commercial Industrial</p>	<p>Suva® 407A R-407A</p> <p>HFC New Equipment Retrofit</p> <p>Lubricant POE</p> <p>Evaporator Temp Medium Low</p> <p>Applications Refrigeration: Commercial Industrial</p>	<p>Suva® 407C R-407C</p> <p>HFC New Equipment Retrofit</p> <p>Lubricant POE</p> <p>Evaporator Temp High</p> <p>Applications AC: Commercial Residential Refrigeration: Commercial</p>	<p>Suva® 410A R-410A</p> <p>HFC New Equipment Only Designed for R-410A</p> <p>Lubricant POE</p> <p>Evaporator Temp High Medium</p> <p>Applications AC: Commercial Heat Pumps Residential</p>
--	---	---	---	---

R-12, Suva® MP39, MP66, R409A REPLACEMENTS*

<p>ISCEON® MO49Plus™ R-437A</p> <p>HFC Retrofit</p> <p>Lubricant MO AB POE</p> <p>Evaporator Temp Medium Low</p> <p>Applications Refrigeration: Commercial Industrial</p>	<p>ISCEON® 39TC® R-423A</p> <p>HFC Retrofit</p> <p>Lubricant POE single lubricant change</p> <p>Evaporator Temp High Medium</p> <p>Applications Centrifugal Chillers</p>	<p>Suva® 134a R-134a</p> <p>HFC New Equipment Retrofit</p> <p>Lubricant POE PAG (auto AC)</p> <p>Evaporator Temp High Medium (Above +20°F /-7°C)</p> <p>Applications Commercial Refrigeration: Appliances Chillers Automotive AC</p>
--	---	---

R-503, R-13 REPLACEMENTS*

<p>Suva® 95 R-508B</p> <p>PFC New Equipment Retrofit (for R-503)</p> <p>Lubricant POE</p> <p>Evaporator Temp Very Low Temp (VLT) Below -40°F</p> <p>Applications Refrigeration: Cascade Systems</p>	<p>Freon® 23 R-23</p> <p>HFC New Equipment Retrofit (for R-13)</p> <p>Lubricant POE</p> <p>Evaporator Temp Very Low Temp (VLT) Below -40°F</p> <p>Applications Refrigeration: Cascade Systems</p>
--	--

*For more detailed information on DuPont Refrigerants and their applications, please visit www.refrigerants.dupont.com and/or www.isceon.com.

SUGGESTED OIL GUIDE

ISCEON® Refrigerant	Recommended Lubricant	Alternate Lubricant
ISCEON® MO99™ (R-438A)	MO	AB - POE
ISCEON® MO79 (R-422A)	MO	AB - POE
ISCEON® MO59 (R-417A)	MO	AB - POE
ISCEON® MO49Plus™ (R-437A)	MO	AB - POE
ISCEON® MO29 (R-422D)	MO	AB - POE
ISCEON® 39TC® (R-423A)	POE (single lubricant change)	

ISCEON® Refrigerants - Oil Change Guidelines

- ISCEON® Refrigerants are compatible with traditional and new lubricants – mineral oil, alkylbenzene and polyol ester. In systems where oil return is a potential concern, replacement of all, or part (10~25%) of the compressor oil charge with an OEM approved polyol ester is recommended.
- ISCEON® 39TC® requires one lubricant change to POE during retrofit. ISCEON® 39TC® tolerates high residual levels of mineral oil; therefore no system flushing is required after changing the original lubricant to POE.

Suva® Refrigerant	Recommended Lubricant	Alternate Lubricant
Suva® 95 (R-508B)	POE	
Suva® 123	MO	AB
Suva® 134a	POE/PAG (Auto AC)	
Suva® 404A	POE	
Suva® 407A	POE	
Suva® 407C	POE	
Suva® 410A	POE	
Suva® 507	POE	

Suva® Refrigerants - Oil Change Guidelines

- Where possible, use OEM-recommended oil type, charge size, and viscosity.
- When converting a CFC or HCFC system to an HFC refrigerant such as Suva® 134a, 407C or 407A, POE is the recommended lubricant. At least 95% of the MO or AB should be replaced with POE of similar viscosity. This typically requires multiple oil changes.

MO = Mineral Oil AB = Alkylbenzene POE = Polyol Ester

Performance Comparison of Retrofit Refrigerants

Refrigerant	Compared to	Discharge Pressure (psi)			Discharge Temp (°F)			Est. Cooling Capacity (%)			Est EER (%)		
		LT*	MT**	HT***	LT*	MT**	HT***	LT*	MT**	HT***	LT*	MT**	HT***
R-22 HFC Replacements													
ISCEON® MO99™	R-22	+3	+6	+5	-22	-45	-31	-6	-8	-7	+7	-1	-2
ISCEON® MO29	R-22	+10	+12		-31	-66		-3	-6		+8	-4	
ISCEON® MO59	R-22		-23	-20		-62	-40		-17	-17		-2	-1
Suva® 407C	R-22		+19	+18		-29	-18		-4	-1		-1	-2
Suva® 407A	R-22	+28	+35		same	-36		-1	+2		+1	-4	
R-502 HFC Replacements													
ISCEON® MO79	R-502	+23	+30		-32	-19		-1	-6		-4	-8	
Suva® 404A	R-502	+21	+27		-20	-10		+1	+1		-2	-3	
Suva® 507	R-502	+29	+36		-22	-12		+2	+2		-2	-3	

*Low Temperature: -25°F evaporator, 105°F condenser, 65°F return gas, 10°F subcooling

**Medium Temperature: 20°F evaporator, 120°F condenser, 65 °F return gas, 10°F subcooling

***High Temperature: 45°F evaporator, 115°F condenser, 65 °F return gas, 10°F subcooling

R-22 assumes demand cooling with discharge temp of 275°F

Refrigerant	Compared to	Discharge Pressure (psi)	Discharge Temp (°F)	Est. Cooling Capacity (%)	Est EER (%)
R-12 HFC Replacements Chillers					
ISCEON® 39TC®	R-12	Same	-20	0 to -5	
ISCEON® MO49Plus™	R-12	+30 to +39	-28 to -16	+4 to +10	-3 to -4
Suva® 134a	R-12	+10	-10	-15*	
R-503, R-13 Replacements					
Suva® 95	R-503	+2	-40	-2	
Freon® 23	R-503	-26	+53	-26	
Freon® 23	R-503	-41	-27	-29	

Performance data based on normal application conditions and is intended to serve as a guide; actual performance will vary depending on system design and conditions.

+ is increase - is decrease

*Capacity loss can be determined by performing an engineered retrofit. Contact DuPont for details.

PRESSURE CONTROL SETTINGS GUIDE

(approximate)


SUPERMARKET REFRIGERATION RETROFITS

This pressure control setting guide provides you with approximate settings that can be used as starting points to help you optimize your system. Recognize that the values expressed can vary with specific conditions, such as actual relative humidity, pressure drop, line sets, equipment location and design. If your current settings for R-22 vary from the baseline values given below, the alternative refrigerant settings will vary proportionally. For more information on retrofits, go to www.refrigerants.dupont.com

Application	Temp Range (°F)	Evap ΔT (°F)	Refrigerant (psig)															
			R-22		ISCEON® MO99™		ISCEON® MO29		ISCEON® MO79		R-404A		R-507		HP80 (R-402A)		R-502	
			Out	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	In	Out	In
Beverage Cooler	35 to 38	15	41	66	38	63	42	69	52	82	53	82	56	86	59	91	50	78
Floral Cooler																		
Produce Cooler																		
Smoked Meat Cooler	32 to 35	15	38	62	35	59	39	64	49	77	49	77	52	82	55	86	47	73
Meat Reach Thru																		
Service Deli																		
Seafood																		
Multi-Deck Fresh Meat	26 to 29	15	32	54	29	51	33	56	42	69	42	68	45	72	47	76	40	65
Frozen Glass Door	-10 to 0	10	9	24	7	21	9	23	14	32	15	33	16	35	37	48	31	41
Frozen Glass Walk-In																		
Frozen Ice Cream	-30 to -20	10	0	10	4 in Hg	8	0	10	4	15	4	16	5	18	6	20	3	15
Frozen Food - Open Type																		

GENERAL RETROFIT GUIDE

For detailed information, please see our retrofit guidelines at www.refrigerants.dupont.com and/or www.isceon.com.



Retrofit examples—no oil change
 R-12 to ISCEON® MO49Plus™
 R-22 to ISCEON® MO99™, MO59, MO29
 R-502 to ISCEON® MO79

*For retrofit to HFC multiple oil changes, DO NOT remove CFC or HCFC refrigerants until AFTER oil flushing is complete.

DuPont Refrigerants

U.S. GENERAL REPLACEMENT GUIDE

R-502, Suva® HP80, HP81, R-408A REPLACEMENTS*		
ISCEON® MO79 R-422A HFC Retrofit Lubricant MO AB POE Evaporator Temp Medium Low Applications Refrigeration: Commercial Industrial	Suva® 404A R-404A HFC New Equipment Lubricant POE Evaporator Temp Medium Low Applications Refrigeration: Commercial Industrial	Suva® 507 R-507 HFC New Equipment Lubricant POE Evaporator Temp Medium Low Applications Refrigeration: Commercial Industrial

R-11 REPLACEMENTS*
Suva® 123 R-123 HCFC New Equipment Retrofit Lubricant MO Evaporator Temp High Medium Applications Centrifugal Chillers

*For more detailed information on DuPont Refrigerants and their applications, please visit www.refrigerants.dupont.com and/or www.isceon.com.

DuPont Refrigerants. The Science of Cool.™

www.refrigerants.dupont.com
www.isceon.com

DuPont Refrigerants
 Chestnut Run Plaza 705-GS29
 P.O. Box 80705
 Wilmington, DE 19880-0705
 U.S.: 1-800-235-7882
 Canada: 1-800-873-7882



The miracles of science™

Copyright © 1997-2011 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™, The Science of Cool™, ISCEON® and Suva® are registered trademarks or trademarks of E. I. duPont de Nemours and Company or its affiliates.

No part of this material may be reproduced, stored in a retrieval system or transmitted in any form or by any means electronic, mechanical, photocopying, recording without the permission of DuPont.

(1/11) [Replaces H-71061-13] Reorder No: H-71061-14