Safety Data Sheet



DuPont[™] Suva[®] 124 Refrigerant

Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DuPont[™] Suva[®] 124 Refrigerant Tradename/Synonym : 1-Chloro-1,2,2,2-Tetrafluoroethane

HCFC-124

Product Grade/Type : ASHRAE Refrigerant number designation: R-124

Product Use : Refrigerant

Restrictions on use : For professional users only.

Manufacturer/Supplier : DuPont

1007 Market Street Wilmington, DE 19898 United States of America

Product Information : +1-800-441-7515 (outside the U.S. +1-302-774-1000)

Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)

Transport Emergency : CHEMTREC: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Product hazard category

Gases under pressure Liquefied gas



Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

Label content

Pictogram :



Signal word : Warning

Hazardous warnings : Contains gas under pressure; may explode if heated.

Hazardous prevention

measures

: Protect from sunlight. Store in a well-ventilated place.

Other hazards

Misuse or intentional inhalation abuse may lead to death without warning., May cause cardiac arrhythmia. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
1-Chloro-1,2,2,2-tetrafluoroethane	2837-89-0	99.7 %

SECTION 4. FIRST AID MEASURES



Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

General advice : Never give anything by mouth to an unconscious person. When symptoms

persist or in all cases of doubt seek medical advice.

Inhalation : Remove from exposure, lie down. Move to fresh air. Keep patient warm and at

rest. Artificial respiration and/or oxygen may be necessary. Consult a physician.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15

minutes. Take off all contaminated clothing immediately. Consult a physician. Wash contaminated clothing before re-use. Treat for frostbite if necessary by

gently warming affected area.

Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15

minutes. Consult a physician if necessary.

Ingestion : Is not considered a potential route of exposure.

Most important

symptoms/effects, acute

and delayed

 Anaesthetic effects Light-headedness irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting,

dizziness or weakness

Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective

equipment.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs,

such as epinephrine, that may be used in situations of emergency life support

should be used with special caution.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

Unsuitable extinguishing

media

: No applicable data available.

Specific hazards : The product is not flammable. Cylinders are equipped with pressure and

temperature relief devices, but may still rupture under fire conditions.

Decomposition may occur.



Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Wear neoprene gloves during cleaning up work after a

fire

Further information : Cool containers/tanks with water spray. Self-contained breathing apparatus

(SCBA) is required if containers rupture and contents are released under fire

conditions.

Water runoff should be contained and neutralized prior to release.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Ventilate area, especially low or enclosed places where heavy vapours might

collect.

Environmental precautions : Should not be released into the environment. In accordance with local and

national regulations.

Spill Cleanup : Ventilate area using forced ventilation, especially low or enclosed places

where heavy vapors might collect.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for

disposal according to local / national regulations (see section 13).

Accidental Release Measures : Avoid open flames and high temperatures. Self-contained breathing

apparatus (SCBA) is required if a large release occurs.

SECTION 7. HANDLING AND STORAGE

Handling (Personnel) : Use sufficient ventilation to keep employee exposure below recommended

limits. Provide sufficient air exchange and/or exhaust in work rooms. For

personal protection see section 8.

Handling (Physical Aspects)

: No applicable data available.

Dust explosion class

: Not applicable

Storage : Valve protection caps and valve outlet threaded plugs must remain in place

4/10



Version 2.0

Revision Date 03/23/2015

Ref. 13000000344

unless container is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems. Never attempt to lift cylinder by its cap. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.

Separate full containers from empty containers. Keep at temperature not exceeding 52°C. Do not store near combustible materials. Avoid area where

salt or other corrosive materials are present.

The product has an indefinite shelf life when stored properly.

Storage period : > 10 yr

Storage temperature : < 52 °C (< 126 °F)

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Use sufficient ventilation to keep employee exposure below recommended

limits. Local exhaust should be used when large amounts are released.

Mechanical ventilation should be used in low or enclosed places.

Personal protective equipment

Respiratory protection : Under normal manufacturing conditions, no respiratory protection is required

when using this product.

Hand protection : Additional protection: Impervious gloves

Eye protection : Wear safety glasses with side shields. Additionally wear a face shield where

the possibility exists for face contact due to splashing, spraying or airborne

contact with this material.

Protective measures : Self-contained breathing apparatus (SCBA) is required if a large release

occurs.

Exposure Guidelines
Exposure Limit Values

1-Chloro-1,2,2,2-tetrafluoroethane

AEL * (DUPONT) 1,000 ppm 8 & 12 hr. TWA



Version 2.0

Revision Date 03/23/2015

Ref. 13000000344

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : gaseous
Form : Liquefied gas
Color : colourless

Odor : slight, ether-like

Odor threshold : No applicable data available.

pH : No applicable data available.

Melting point/freezing point : Freezing point

-199 °C (-326 °F)

Boiling point/boiling range : Boiling point

-12.0 °C (10.4 °F) at 1,013 hPa

Flash point : does not flash

Evaporation rate : No applicable data available.

Flammability (solid, gas) : The product is not flammable.

Upper explosion limit : Method: None per ASTM E681

Lower explosion limit : Method: None per ASTM E681

Vapor pressure : 3,827 hPa at 25 °C (77 °F)

Vapour density : No applicable data available.

Density : 1.355 g/cm3 at 25 °C (77 °F)

(as liquid)

Specific gravity (Relative

density)

: 1.36 at 25 °C (77 °F)

^{*} AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.



Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

Water solubility : 1.45 g/l at 25 $^{\circ}$ C (77 $^{\circ}$ F) at 1,013 hPa

Solubility(ies) : No applicable data available.

Partition coefficient: n-

octanol/water

: No applicable data available.

Auto-ignition temperature : No applicable data available.

Ignition temperature : no data available

Decomposition temperature : No applicable data available.

Viscosity, kinematic : No applicable data available.

Viscosity : No applicable data available.

% Volatile : 100 %

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable at normal ambient temperature and pressure.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Polymerization will not occur.

Conditions to avoid : Avoid open flames and high temperatures.

Incompatible materials : Alkali metals Alkaline earth metals, Powdered metals, Powdered metal salts

Hazardous decomposition

products

Decomposition products are hazardous., This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming by drophloric and by drophloric and possibly carbonyl halides. These

hydrochloric and hydrofluoric acids, and possibly carbonyl halides., These materials are toxic and irritating., Avoid contact with decomposition products

SECTION 11. TOXICOLOGICAL INFORMATION

1-Chloro-1,2,2,2-tetrafluoroethane

Inhalation 4 h LC50 : > 230000 ppm , Rat Anaesthetic effects

Central nervous system effects

7/10



Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

Inhalation Low Observed

Adverse Effect

Concentration (LOAEC)

Inhalation No Observed

Concentration

Adverse Effect

Cardiac sensitization Skin irritation

Not expected to cause skin irritation based on expert review of the

properties of the substance.

: 25000 ppm, Dog Cardiac sensitization

: 10000 ppm, Dog

Eye irritation Not expected to cause eye irritation based on expert review of the

properties of the substance.

Skin sensitization Not expected to cause sensitization based on expert review of the

properties of the substance.

Does not cause respiratory sensitisation.,

There are no reports of human respiratory sensitization.

Repeated dose toxicity Inhalation

multiple species

No toxicologically significant effects were found.

Carcinogenicity Not classifiable as a human carcinogen.

Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic

effects.

Animal testing did not show any mutagenic effects.

Teratogenicity : Animal testing showed no developmental toxicity.

Further information : Cardiac sensitisation threshold limit : 140000 mg/m3

Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or those found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition).

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

Safety Data Sheet



DuPont[™] Suva[®] 124 Refrigerant

Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

SECTION 12. ECOLOGICAL INFORMATION

Additional ecological information : no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste disposal methods -

Product

IMDG

: Can be used after re-conditioning. Recover by distillation or remove to a

permitted waste disposal facility. Comply with applicable Federal,

State/Provincial and Local Regulations.

Contaminated packaging : Empty pressure vessels should be returned to the supplier.

SECTION 14. TRANSPORT INFORMATION

DOT UN number : 1021

Proper shipping name : 1-Chloro-1,2,2,2-tetrafluoroethane

Class : 2.2 Labelling No. : 2.2

IATA_C UN number : 1021

Proper shipping name : 1-Chloro-1,2,2,2-tetrafluoroethane

Class : 2.2 Labelling No. : 2.2 UN number : 1021

Proper shipping name : 1-CHLORO-1,2,2,2-TETRAFLUOROETHANE

Class : 2.2 Labelling No. : 2.2

SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated : 1-Chloro-1,2,2,2-tetrafluoroethane

9/10



Version 2.0

Revision Date 03/23/2015 Ref. 130000000344

Chemical(s)

NJ Right to Know

: Substances on the New Jersey Workplace Hazardous Substance List present

Regulated Chemical(s)

at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): 1-Chloro-1,2,2,2-tetrafluoroethane

California Prop. 65

: Chemicals known to the State of California to cause cancer, birth defects or

any other harm: none known

SECTION 16. OTHER INFORMATION

Suva is a registered trademark of E. I. du Pont de Nemours and Company Before use read DuPont's safety information.

For further information contact the local DuPont office or DuPont's nominated distributors.

[®] DuPont's registered trademark

Revision Date : 03/23/2015

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.