QSWI1000

The safe & affordable install

Applicable for residential or light commercial installations

Quick Swivel SPECS
QSWI1000

A Close Up:

Each arm attaches to wood using 2 zip screws for stability & a 4” through bolt & wing nut for security.
It can also be installed to steel using our steel beam adapters.

Extension arms individually adjust in 1” increments using thumb screws & wing nuts for speed & versatility. This “U” mount installs as high as 19.5” or as low as 27.5” on flat or pitched roofs.



Our Quick Swivel is made with 14-gauge steel able to hold 200 lbs. The swivel allows for 360 degree rotation for setting the perfect direction of air flow.

*Powder Coated.

12 points of anti-vibration isolation is provided along with 3 hitch pins for the “H” bracket. This adds to the safety & sturdiness of the Quick Swivel.

Installation can be accomplished in minutes because all necessary hardware is provided. Attaching a Quick Swivel to your unit is fast & stress-free.

The Quick Swivel can easily be installed in residential or commercial applications. Turn the Swivel in any direction you need, then lock it in place.

Quick-Sling’s Quick Swivel provides you with a non-swinging, rotating platform that is quick, safe, stable and affordable.

Patent Pending

Quick-Sling 391 West Water Street Taunton, MA 02780 P:1.800.699.0453 F:1.800.699.0423
www.Quick-Sling.com

*As of 1/1/2015 Quick-Sling offers a 2-year warranty on steel & workmanship; Quick-Sling products are coated in accordance with ASTM D3451-06.