

Model: AGA5568EXT
Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 200-230V 3~ 60Hz 200-220V 3~
 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	220V 3~ 50HZ	56200	14162	16467	6150	9.14	2.3	2.68	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)
ASHRAE	230V 3~ 60HZ	68000	17136	19924	7100	9.58	2.41	2.81	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 101
Weight Unit of Measure: LB
Displacement (cc): 124.319
Oil Type: N/A
Viscosity (cSt): N/A
Oil Charge (cc): 1955

Electrical

Voltage Range (50 Hz): 180-242
Voltage Range (60 Hz): 180-254
Locked Rotor Amps (LRA): 135
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 20
Max. Continuous Current (MCC in Amps): 33.6
Motor Resistance (Ohm) - Main: .614
Motor Resistance (Ohm) - Start: N/A
Motor Type: 3PH
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, cURus Recognized