

Model: AJA7465AXA

Product Description

Type: Reciprocating
Application: MBP – Medium Back Pressure
Refrigerant: R-12
Voltage/Frequency: 115V ~ 60Hz 100V ~ 50Hz
Version: N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	6650	1676	1948	1135	5.86	1.48	1.72	-6.7°C (20°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -23.3°C to -1.1°C (-10°F to 30°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 54
Weight Unit of Measure: LB
Displacement (cc): 32.678
Oil Type: Synthetic Alkylate
Viscosity (cSt): 32
Oil Charge (cc): 664

Electrical

Voltage Range (50 Hz): 90-110
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 68
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 11.6
Max. Continuous Current (MCC in Amps): 16
Motor Resistance (Ohm) - Main: .48
Motor Resistance (Ohm) - Start: 3.06
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

cURus Recognized