

Model: AKA4476YXA
Product Description

Type: Reciprocating
Application: HBP - High Back Pressure
Refrigerant: R-134a
Voltage/Frequency: 115V ~ 60Hz 100V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
ARI	115V ~ 60HZ	7680	1935	2250	1070	7.18	1.81	2.1	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	18.3°C (65°F)	46°C (115°F)

General

Evaporating Temp. Range: -6.7°C to 12.8°C (20°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 41
Weight Unit of Measure: LB
Displacement (cc): 22.599
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 512

Electrical

Voltage Range (50 Hz): 90-110
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 58.8
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 11.3
Max. Continuous Current (MCC in Amps): 16
Motor Resistance (Ohm) - Main: .59
Motor Resistance (Ohm) - Start: 4.22
Motor Type: CSIR
Overload Type: N/A
Relay Type: N/A

Agency Approval

cURus Recognized