

Model: AKA5470EXA
Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 115V ~ 60Hz 100V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ASHRAE	115V ~ 60HZ	7000	1764	2051	800	8.75	2.21	2.56	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 37
Weight Unit of Measure: LB
Displacement (cc): 12.815
Oil Type: Synthetic Alkylate
Viscosity (cSt): 32
Oil Charge (cc): 512

Electrical

Voltage Range (50 Hz): 90-110
Voltage Range (60 Hz): 103-127
Locked Rotor Amps (LRA): 35
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 7.1
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 1.043
Motor Resistance (Ohm) - Start: 9.907
Motor Type: PSC
Overload Type: N/A
Relay Type: N/A

Agency Approval

cURus Recognized