

**Model: AVB5558EXT**
**Product Description**

**Type:** Reciprocating  
**Application:** HBP/AC - Air Conditioning  
**Refrigerant:** R-22  
**Voltage/Frequency:** 200-230V 3~ 60Hz 200-220V 3~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ARI	230V 3~ 60HZ	57000	14364	16701	5400	10.56	2.66	3.09	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	18.3°C (65°F)	46°C (115°F)

**General**

**Evaporating Temp. Range:** -23.3°C to 12.8°C (-10°F to 55°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 89  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 91.035  
**Oil Type:** Synthetic Alkylate  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 1624

**Electrical**

**Voltage Range (50 Hz):** 180-242  
**Voltage Range (60 Hz):** 180-254  
**Locked Rotor Amps (LRA):** 110  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 15.7  
**Max. Continuous Current (MCC in Amps):** 26  
**Motor Resistance (Ohm) - Main:** .82  
**Motor Resistance (Ohm) - Start:** N/A  
**Motor Type:** 3PH  
**Overload Type:** N/A  
**Relay Type:** N/A

**Agency Approval**

cURus Recognized