

Model: AWG5524EXN
Product Description

Type: Reciprocating
Application: HBP/AC - Air Conditioning
Refrigerant: R-22
Voltage/Frequency: 208-230V ~ 60Hz 200-220V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ARI	230V ~ 60HZ	24200	6098	7091	2480	9.76	2.46	2.86	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	18.3°C (65°F)	46°C (115°F)

General

Evaporating Temp. Range: -23.3°C to 12.8°C (-10°F to 55°F)
Motor Torque: Low Start Torque (LST)
Compressor Cooling: Fan

Mechanical

Weight: 60
Weight Unit of Measure: LB
Displacement (cc): 43.1
Oil Type: Synthetic Alkylate
Viscosity (cSt): 32
Oil Charge (cc): 1141

Electrical

Voltage Range (50 Hz): 180-242
Voltage Range (60 Hz): 197-254
Locked Rotor Amps (LRA): 60
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 11
Max. Continuous Current (MCC in Amps): 18.3
Motor Resistance (Ohm) - Main: 1.09
Motor Resistance (Ohm) - Start: 2.53
Motor Type: PSC
Overload Type: N/A
Relay Type: N/A

Agency Approval

cURus Recognized