

**Model: AWG5528EXN**
**Product Description**

**Type:** Reciprocating  
**Application:** HBP/AC - Air Conditioning  
**Refrigerant:** R-22  
**Voltage/Frequency:** 208-230V ~ 60Hz 200-220V ~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
ARI	230V ~ 60HZ	28000	7056	8204	2870	9.76	2.46	2.86	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	18.3°C (65°F)	46°C (115°F)

**General**

**Evaporating Temp. Range:** -23.3°C to 12.8°C (-10°F to 55°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 62  
**Weight Unit of Measure:** LB  
**Displacement (cc):** 48.427  
**Oil Type:** Synthetic Alkylate  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 1141

**Electrical**

**Voltage Range (50 Hz):** 180-242  
**Voltage Range (60 Hz):** 197-254  
**Locked Rotor Amps (LRA):** 73  
**Rated Load Amps (RLA 50 Hz):** 0  
**Rated Load Amps (RLA 60 Hz):** 13  
**Max. Continuous Current (MCC in Amps):** 22  
**Motor Resistance (Ohm) - Main:** .88  
**Motor Resistance (Ohm) - Start:** 2.1  
**Motor Type:** PSC  
**Overload Type:** N/A  
**Relay Type:** N/A

**Agency Approval**

cURus Recognized